

AMENDMENTS TO THE SPECIFICATION

I. Please replace the SPECIFICATION, pages 1-23, with the following amended Specification:

BACKGROUND OF THE INVENTION

1. Field of the invention

The present invention relates to an artificial miniature landscape model which ~~are~~ is ornamented with three dimensionally variable colored LEDS.

2. Description of the Prior Art

The conventional illuminated decorative potted ~~plants~~ plant displays which can be bought from the markets are usually formed of a fixture containing an incandescent lamp. As it is well known that the incandescent lamp has several inherent disadvantages of a low efficiency, a short lifetime and a low light intensity, it is therefore ~~it is~~ not suitable for use where ~~the~~ ample color variation and light intensity are required.

Besides, ~~in stead~~ instead of the incandescent lamp, LEDS

~~are have been~~ installed in the bottom cavity of a rotatable pot to illuminate the potted plant upwardly from the bottom. However, ~~however,~~ the bottom of the pot often interrupts transmission of the light beam of the LEDS, ~~to illuminate the plat~~ thereby considerably lowering the lighting effect.

In view of this, a light source ~~is~~ has been introduced to the flower with an optical fiber conductor, but as the light source is a spot light affixed to the flower without ~~matching~~ being matched with the contour of the flower, ~~so that there will be in~~ is a lack of a three dimensionally vivid and appealing display. For ~~For~~ ~~[[,]]~~ ~~and for~~ demonstration of an active feeling, the pot is rotated by a driving motor together with a color disc, thereby always causing inevitable noise from the rotating motor and shortening the durability of the light source.

SUMMARY OF THE INVENTION

Aiming at the above depicted defects inherent to the prior techniques, the present invention ~~is to propose~~ provides a newly developed construction of an artificial miniature landscape model with three dimensionally variable colored LEDS (~~or~~ also

called multi-colored LEDS), wherein variable colored LEDS are affixed ~~to~~ within a molded transparent resin structure of artificial flowers, fruits, birds, leaf leaves, and ~~butterfly~~ butterflies so as to exhibit a three dimensionally variable colored lighting effect of the LEDS contained in the transparent molded resin structure.

The main structure of the first embodiment comprises an artificial miniature landscape model with three dimensionally colored LEDS and is essentially composed of a plurality of automatic color variable LEDS, metallic conductor submains, heat shrink bushings or heat resisting insulation tube plugs, externally or internally threaded tube connectors, electrically insulated ~~insulation~~ conductors, a low voltage rectifier, flowers, leaf blades, fruits, birds, butterflies, coniferous Christmas trees formed into molded transparent resin structures, and pots.

Wherein, the ~~it is characterized in that said~~ LEDS are sealed in ~~said~~ the molded transparent resin structure ~~with~~ at a certain properly inclined angle. The ~~, said~~ submains of the potted plant are constructed of a plurality of various sized (diameters) copper tubes bent and welded, and ~~being~~ are assembled section by section with screws engaging;

The root of a trunk of said potted plant is provided with two flanges and is fixed into ~~said the~~ the pot with a binder made of mixed resin and ~~ballasts~~, ballast material. The ~~the~~ electricity is ~~supply~~ supplied from a low voltage rectifier via a power supply switch to ~~said the~~ the LEDS.

The above objects and other advantages of the present invention will become more apparent by describing in detail the preferred embodiments of the present invention with reference to the following attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an assembly view of a potted plant with flowers and a butterfly resting on a flower corolla;

Fig. 2 is an assembly view of a potted plant with flowers, fruits and birds perching on a tree branch;

Fig. 3 is a schematic view of a potted Christmas tree;

Fig. 4 is a schematic view showing the assembled structure of a pot with solid copper conductors with flanges;

Fig. 5 is a schematic view of an LED affixed to a leaf;

Fig. 6 is a schematic view showing a group of LEDS ~~are~~ affixed to a flower and a leaf;

Fig. 7 is a schematic view showing how a butterfly together with LEDS is supported;

Fig. 8 is a schematic view showing a bird with LEDS ~~perches~~ perched on a tree branch;

Fig. 9 is a schematic view showing a fruit affixed with LEDS;

Fig. 10 is a schematic view showing a coniferous leaf of a Christmas tree affixed with an LED;

Fig. 11 is a schematic view of a potted ~~plant~~ of African daisy_(sunflower) plant with LEDS;

Fig. 12 is a schematic view of a potted ~~plant~~ of tulip plant with LEDS;

Fig. 13 is a schematic view of a potted ~~plant~~ of orchid plant with LEDS;

Fig. 14 is a schematic view showing an artificial orchid with LEDS;

Fig. 15 is a schematic view showing a group of LEDS and an A connector;

Fig. 16 is a schematic view showing a group of LEDS and a B connector;

Fig. 17 is a schematic view showing a potted plant of calla

lily flowers connected with A connectors;

Fig. 18 is a schematic view showing a potted plant of hyacinth flowers connected with B connectors;

Fig. 19 is a schematic view showing a potted plant of rose flowers connected with both A and B connectors

Fig. 20 is an exploded view of a medium or large ~~sized~~ size potted plant;

Fig. 21 is an assembly view of medium or large ~~sized~~ size potted plant;

Fig. 22 is a schematic view showing an electrical circuit layout in the rear of a pot;

Fig. 23 and 23A are schematic views showing how the flowers of a medium or small ~~sized~~ size potted plant are assembled;

Fig. 24 is an assembly view of a medium or small size ~~sized~~ potted plant (1);

Fig. 25 is an assembly view of a medium or small size ~~sized~~ potted plant (2)

Fig. 26 is a schematic view showing a spruce and LEDS ~~annected~~ connected with optical fibers;

Fig. 26A is a schematic view showing two ~~spades~~ flowers

~~are~~ connected with optical fibers;

Fig. 27 is a schematic view of a potted plant equipped with a water spray damper and a water circulating system; [['']]

Fig. 28 is an ~~ideol~~ statue of a fishing raccoon illuminated with LEDS;

Fig. 29 is an illustrative view showing the ~~way~~ method of inserting a heat resisting insulation plug into a copper tubular submain;

Fig. 30 is an illustrative view showing the ~~way~~ method of fitting a solid copper branch into an internally threaded copper alloy connector;

Fig. 31 is a schematic view of an artificial orchid being plugged in an A connector;

Fig. 32 is a schematic view of an artificial coniferous Christmas tree being fitted into a copper tubular branch with a heat resisting insulation plug;

Fig. 33 is a schematic view of an internally threaded copper alloy connector;

Fig. 34 is a schematic view of an externally threaded copper alloy connector;

Fig. 35 is a schematic view showing the ~~way~~ method of

fixing LEDS to a PCB in the body of an artificial butterfly;

Fig. 36 is a schematic view showing the ~~way~~ method of connecting LEDS to an A connector in the body of a bird ~~idol~~ statue;

Fig. 37 is a detailed view illustrating how the LEDS are connected to a B connector in the body of a bird ~~idol~~ statue;

Fig. 38 is a miniature model landscape wherein a bear ~~raccoon-idol~~ statue is resting under the maple tree;

Fig. 39 is a schematic view showing several metallic conductor branches ~~are~~ connected to one main conductor tube;

Fig. 40 is a schematic view in which several forms of connecting LEDS to a slim copper alloy tube ~~[[,]]~~ are shown;

Fig. 41 is a schematic view of an LED illuminated potted ~~LED-illuminated~~ African daisy (sunflower) ~~being~~ assembled with A connectors;

Fig. 42 is a schematic view of an LED illuminated potted ~~LED-illuminated~~ tulip ~~being~~ assembled with A connectors;

Fig. 43 is a schematic view of a medium ~~sized~~ size potted calla lily, with LEDS and a soft FPC ~~EPC~~ sealed in the molded transparent resin structures and formed along the rear surface of the flower and the leaf;

Fig. 44 is a schematic view showing a funnel shaped molded transparent resin structure is formed at the torus of the daffodil for sealing LEDS in there;

Fig. 45 is schematic view showing a funnel shaped molded transparent resin structure is formed at the torus of an Anthurium scherzerianum and having an aperture at the bottom of the leaf stalk;

Fig. 45A is a schematic view showing a funnel shaped molded transparent resin structure is formed at the bottom of a maple leaf stalk;

Fig. 46 is a schematic view showing a cone shaped molded transparent resin structure is formed at the torus of an orchid;

Fig. 47 is a schematic view showing a funnel shaped molded transparent resin structure is formed at the leaf stalk of a cala lily;

Fig. 48A is a schematic view showing various types of electrical connectors employed by the present invention;

Fig. 48B is another schematic view showing various types of electrical connectors employed by the present invention;

Fig. 49 is a front schematic view showing a U or V shaped aperture formed at the stalk of a heptagonal leaf;

Fig. 50 is a rear view of Fig. 49;

Fig. 51A is a schematic assembly view showing a multi-colored light element composed of a plurality of R.G.B original color light emission dies and its control IC ~~are implanted~~ on a PCB and then connected to an A type connector according to the present invention;

Fig. 51B is a schematic assembly view showing a multi-color light element composed of a plurality of R.G.B original color light emission dies and its control IC ~~are implanted~~ on a PCB and then connected to a B type connector according to the present invention; and

Fig. 52 is a schematic assembly view showing a multi-color light element composed of a plurality of R.G.B original color light emission dies and its control IC ~~are implanted~~ on an PCB FPC and then connected to a threaded tubular connector according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Several embodiments of the present invention will be

~~described~~ described in detail with reference to the attached drawings hereinbelow;

Embodiment 1:

Referring to Figs. 1, 2, 3, 11, 12, 13, 14, 32, The main structure of the first embodiment comprises a plurality of automatically color variable LEDS 5 (or called multi-colored LEDS), metallic conductor branches 14, electrically insulated ~~insulation~~ conductors 2, heat shrink bushings, or ~~insulation~~ insulated tubular plugs, or internally or externally threaded tubular connectors 15 (see Figs. 33, 34), a low voltage rectifier 12, base connectors 22, flowers 23, leaf blades 24, birds, fruits, butterflies, a molded coniferous Christmas tree(Fig. 10), and pots 13. The LED 5 is color variable. A plurality of LEDS 5 are sealed in a molded transparent resin structure formed between a leaf stalk 6 and a leaf blade, on a torus 1 beneath the center of the flower, or in the chest of a butterfly 19. In case the flower has no torus (such as orchid, daffodil, see Figs. 44, 46 [[76]]), or the ~~leaf~~ leaf blade ~~with~~ has a narrow ~~elongated~~ elongated leaf stalk (see Fig. 47). or the flower ~~with~~ has a slim torus, a cone shaped or a funnel shaped molded transparent resin structure 151 may be formed beneath the rear of the leaf blade so as to

~~accommodated~~ accommodate the LEDS 5 and a PCB. For other types of leaf blades, such as colla lily, the plants with heptagonal leaves (see Figs. 49, [[.]] 50), anthurium sherzerianum (see Fig. 45), and a maple leaf (Fig. 45A), a cone or a funnel shaped molded transparent resin structure is formed at the bottom of the leaf stalk and provided with an aperture in correspondence with a U or V shaped aperture 153 along the leaf blade of a real plant. The leaf blade 24 (see fig. 5), the flower 23 (see Fig. 6), the butterfly (see fig. 7), the bird (see Fig. 8), the fruit (see Fig. 9), and the coniferous Christmas tree (see Fig. 10), ~~are all~~ can all be formed ~~into~~ with a ~~molded~~ molded resin structure to exhibit a colorful LED lighting variation on their surface. In order to enhance the degree of color and ~~line of~~ their silhouette, the molded transparent resin structure can be entirely or partially sand ~~sprayed~~ blasted to form a foggy (diffused) surface, or partially ~~color~~ painted with color, or partially semi-transparently ~~color~~ sprayed with color, so as to create an effect of layering color variation. Incidentally, the artificial butterfly feelers may employ optical fibers 40 affixed to its head.

The plant trunk 8 and branch 9 of various flowers 23, leaf

blades 24 fruits, butterflies, birds and Christmas trees formed of molded transparent resin structures are formed ~~of~~ with metallic tubular submains 14 which ~~being a bunch of~~ are a plurality of flexible and various sized metallic copper conductor tubes, copper alloy tubes, or metal plated (silver or tin) tubes ~~to~~ welded together. They can be ~~flexed~~ bent into a desired angle and coated with various colored resins ~~painting~~, a color resin ~~painting~~ paint or a resin and stone ~~power~~ powder mixture 39 and then wrapped with a cotton tape to increase its diameter. The positive terminal pins 17 of the LED ~~which being parallelly~~ are welded ~~with~~ to a slim electrically insulated ~~insulation~~ conductor 2 ~~is and~~ inserted into a heat shrink insulation bushing 15. After having been shrunk ~~[[,]] after it has shrunk~~ by heating, it is inserted into the metallic tubular submain 14 and fixed at thereat. All slim electrically insulated ~~insulation~~ conductors 2 are gathered at the lower chamber 26 of the pot via the metallic tubular submain 14 and ~~welded~~ welded to one terminal of the power supply switch, while the other terminal thereof is connected to the positive terminal of the base connector 22. The ~~the~~ negative terminal pins 18 of the LEDS 5 are welded to the wall surface of the metallic tubular submain 14, so that the

~~submain~~ submain 14 becomes a negative side conductor. Alternatively, the positive terminal, Pins 17 of the LEDS 5 are ~~stranded~~ twisted together and welded to a positive electric conductor 2 and passed through the middle pathway of the insulated tubular plug (see Fig. 29), while the negative terminal pins 18 of the LEDS 5 are respectively welded to the outer wall of the metallic tubular submain 14, or fixed to the outer wall of the insulation tubular plug and then plugged into the tubular submain 14. To prevent the plug from falling out, ~~and~~ a check ring 110 is provided to the plug, or ~~forming~~ two indentations 147 (see Fig. 29) are formed by slightly punching the end of the tubular submain 14, or applying an externally or internally threaded set screw at the end of the submain 14 (see Figs. 33, 34), ~~so as to prevent the plug from slipping out.~~ One end of the conductor is welded to a welding terminal provided at the other end of the submain 14, ~~[[;]]~~ while the other end of the conductor is welded to the negative terminal of the base connector 22. Using the internally and externally threaded set screw, or check ring to retain the tubular plug makes the structure of the present embodiment easy to construct with low cost.

As shown in Figs. 1, 2, 3 and 19, the branch 9 and the trunk 8 may be assembled section by section using a combination of male and female ~~combination of~~ copper alloy joints 132, and then filling the clearance with soft silicon rubber ~~and coating~~ that is then coated with a colored resin painting paint. The trunk 8 ~~having~~ has two flanges 20 at its a bottom portion thereof, and is set ~~at~~ in the upper chamber 25 with the mixture of the resin and ~~ballasts~~ ballast material. The power is supplied to the LEDS 5 from a power supply switch 11 through a low voltage rectifier 12. With this arrangement, as shown in Figs. 13 and 14 a novel, delicate and exquisite decorative artificial potted ~~plants~~ plant display with three dimensionally variable colored LEDS5 can be created in which the leaf blade 24, the flower 23, the butterfly, the bird, the fruit, and the Christmas tree can all be formed into a molded resin structure to exhibit a vivid colorful lighting variation. The degree of color and the ~~line of~~ silhouette of the display is intensified by entirely or partially sand ~~spraying~~ blasting the above molded transparent resin structure 38. Besides, the extra artifacts made of the mixture of ~~the~~ resin and stone powder ~~accompanied with~~ added to the plant display further increase exquisiteness.

(Embodiment 2)

Referring to Fig. 4 in this embodiment, the plant trunk 8 and branch 9 of ~~various flowers 23, leaf blades 24 fruits, birds and trees formed,~~ the metallic tubular ~~submain~~ submain 14 is are formed of a plurality of flexible various sized ~~copper~~ copper bars. The slim electrically ~~insulation~~ insulated conductor 2 ~~pierces~~ passes through the large aperture 118 opened at the upper portion of an internally threaded copper alloy connector ~~111~~ 116 (see Fig. 30) and twists along the submain 14 to enter the pot. The diameter of the submain is enlarged by wrapping the electrically ~~insulation~~ insulated conductors 2 with a cotton tape 41 and the copper bar 21 ~~for~~ with several layers, and then coating with colored resin ~~painting~~ paint or the mixture of resin ~~painting~~ paint and a stone ~~power~~ powder mixture 39.

The slim electrically ~~insulation~~ insulated conductors 2 connected to one terminal of LEDS 5 are connected to the positive terminal of the power supply switch 11 provided at the base of the lower pot chamber 26 via three apertures 7 opened on the two flanges. The ~~The~~ ~~[[;]]~~ while the other negative terminal pins of the LEDS 5 are welded to the small apertures 118 ~~opened on~~ formed in the copper alloy conductors 116 which

~~being are~~ screwed ~~combined~~ onto the copper bars 21 forming the metallic tubular submain 14, so that the submain 14 serves as a negative conductor. The welding terminal plate provided on the copper bar at the trunk bottom is the other terminal of the ~~submain~~ submain 14. ~~A~~ a conductor which ~~being~~ is welded to ~~it~~ the submain 14 ~~has~~ extends its other end ~~and~~ is welded to the base connector 22 in the lower pot ~~chamber~~ chamber 26, so as to serve as a negative terminal and thereby ~~providing~~ provides the means for the leaf blades 24, the flowers 23, the fruits and the birds coupled to the submain 14 to exhibit a variety of color change.

(Embodiment 3)

Referring to Figs. 15, 17, 19 and 31, in this embodiment, the present invention comprises the LEDS 5, the metallic tubular submain 14, the electrically insulation ~~insulated~~ conductors 2, a PCB 37, an insulation material 28, positive terminal pins 29, an inner tube 30, an A connector 31, a colored soft plastic bushing 33, an ~~[[a]]~~ A receptacle 32, flowers 23, leaf blades 24 fruits, butterflies of a molded transparent resin structure, and pots 13. The plant trunk 8 and branches 9 of the metallic tubular submain 14 ~~which-being are~~ a ~~bunch-of-a~~

plurality of flexible and various sized metallic copper conductor tubes, copper alloy tubes, or metal plated (silver or tin) tubes ~~to~~ welded together. They can be flexed into a desired angle and coated with various colored resin ~~painting~~ paints, a ~~color resin painting~~ or a resin and stone ~~power~~ powder mixture 39 and then wrapped with a cotton tape 41 to increase its diameter.

Wherein the positive terminal pins ~~29~~ 17 of the LEDS 5 ~~which being~~ are connected in parallel or are individually welded to the pin holes formed on a copper foil at the upper surface of the PCB 37. The ; ~~while the~~ negative terminal pins 18 of the LEDS 5 are welded to the negative side pin holes of the copper foil formed on the rear edge surface of the PCB 37. The positive terminal pins of the LEDS 5 and the positive terminal pins 29 are mutually connected, but the housing of the A connector 31 and the positive terminal pins 29 are isolated by the insulation material 28.

The A connector 31 is fitted into the A receptacle 32 ~~so as to insert~~ with the positive terminal pin 29 inserted into the inner tube 30. ~~the~~ The lower end of the inner tube 30 is welded to the electrically ~~insolation~~ insulated conductor 2 so as to form a positive tube conductor. The ; ~~while the~~ bottom edge of the A

receptacle 32 is welded or ~~screw~~ threadedly engaged to the metallic tubular ~~submain~~ submain 14 so as to provide a negative conductor. Then afterwards, the LEDS 5 are sealed in the molded transparent resin structure and the colored soft plastic bushing 33 is compressed onto the A connector 31 and the A receptacle 32. In this version, the molded structure of the flowers and leaves can be efficiently replaced or ~~changed~~ their position changed, if desired.

(Embodiment 4)

Referring to Figs. 16, 18 and 19, in this embodiment, the present invention ~~comprises~~ comprises a plurality of automatically color variable LEDS 5, flowers 23, leaf blades 24, birds, fruits, butterflies, metallic conductor branches 14, electrically ~~insulation~~ insulated conductors 2, PCB 37, insulation material 28, positive terminal pins 29, inner tube 30, B connector 34, colored soft plastic bushing 33, B receptacle 35, and pots 13. The B connector 34 and a B receptacle 35 in which a groove 148 is formed along the outer edge of the B connector 34, is inlaid into a flange 149 formed in the B receptacle 35. The trunk 8 and the branches 9 are both coated with the colored resin ~~painting~~ paint, or the ~~trunk~~ trunk 8 is

covered by a molded structure formed of the mixture of the resin and the stone powder 42 (see Fig. 18). Here, the PCB ~~[[48]]~~ 43 is welded to the bottom outer wall of the trunk 8 so as to ~~weld~~ connect the negative terminal pins of the LEDS 5 to the surface of the trunk 8 via a negative copper foil. A ; ~~while a~~ positive copper foil provided at the outer edge of the PCB 43 is welded to a positive conductor together with the positive terminal pins of the LEDS 5 and inserted into a small aperture 3 formed on the bottom surface of the trunk 8. A pistil 40 formed of an optical fiber (see Fig. 18) is connected to and stuck at the center portion of the molded flower structure near the head of the LEDS 5 ~~with an optical fiber~~. The color light is directed by the optical fiber to its exposed round head.

Wherein the positive terminal pins ~~29~~ 17 of the LEDS 5 ~~which being~~ are connected in parallel ~~are~~ and welded to the pin holes formed on a copper foil at the upper surface of the PCB 37 for connection to the corresponding terminal pin 29. The ; ~~while the~~ negative terminal pins 18 of the LEDS 5 are welded to the negative side pin holes of the copper foil formed on the rear edge surface of the PCB 37. The positive terminal pins 17 of the LEDS 5 and the positive terminal pins 29 are mutually

connected, but the housing of the A connector 31 and the positive terminal pins 29 are isolated by the insulation material 28.

The B connector 34 is fitted into the B receptacle 35 so as to insert the positive terminal pin 29 into the inner tube 30. ~~the~~ The lower end of the inner tube 30 is welded to the electrically ~~insolation~~ insulated conductor 2 so as to form a positive tube conductor. The ; ~~while the~~ bottom edge of the B receptacle 35 is welded or ~~screw~~ threadedly engaged to the metallic tubular ~~submain~~ submain 14 so as to provide a negative conductor. Then afterwards, the LEDS 5 are sealed in the molded transparent resin structure and the colored soft plastic bushing 33 is compressed onto the B connector 34 and B receptacle 35. In this version, the molded structure of the flowers and leaves can be efficiently replaced or ~~changed~~ their position changed, if desired.

(Embodiment 5)

Referring to Figs. [[21]] 20 through 22, this embodiment is composed of a plurality of automatically color variable LEDS 5, flowers 23, leaf blades 24, birds, fruits, butterflies, metallic conductor branches 14, electrically insulated ~~insolation~~

conductors 2, negative metallic base plate 74, A connector 31, A receptacle 32, B connector 34, B receptacle 35, artifact 55, miniature ~~lands-cape~~ landscape 56, and pots 13, the plant trunk 8 and branches es 9 of various flowers 23, leaf blades 24 fruits, birds and trees formed, the embodiment 3 using the A connector 31 and the A receptacle 32 and the embodiment 4 using the B connector 34 and the B receptacle 35. A colored miniature landscape 56 is molded with mixture of resin, stone powder and ~~fiber-glass~~ fiberglass, the artifact 55 thereon is made of a molded transparent resin structure with LEDS 5. The clearance between the flange 36 around the artifact 55 and an indentation around the upper edge thereof is filled with a soft resin and is ~~color~~ painted with a color. For decoration of the miniature ~~lands-cape~~ landscape 56, instead of a sponge groove 111, a ~~bunch~~ plurality of slim vines are inserted on a sponge 97 so as to serve as a ~~suspention-mustache~~ hanging ornament 82 (see Fig. 21).

Wherein the positive terminal pins 17 of the LEDS 5 ~~which being~~ are connected in parallel ~~are~~ and welded to the pin holes formed on a copper foil 54 at the upper surface of the PCB 57. The ; ~~while-the~~ negative terminal pins 18 of the LEDS 5 are welded to the negative side pin holes of the copper foil formed

on the rear edge surface of the PCB 57.

A copper tube 58 is welded to the negative copper foil of the PCB 57 to serve as a negative conductor. The terminal pin of the copper tube 58 ~~penetrates~~ passes through the miniature landscape 56 and is fixed to a negative metallic base plate 74 with a nut and washer combination 75. The ; ~~while the~~ negative metallic base plate 74 is sustained on the pot by stands 51 and a barrier plate 52 (see Fig. 22).

(Embodiment 6)

Referring to Figs. 23 and 24, ~~in this embodiment~~, this embodiment is composed of a plurality of automatically color variable LEDS 5, decorative foliage 70, A connector 31, A receptacle 32, B connector 34, B receptacle 35, coil spring 71, receptacle 72, negative copper alloy tube 73, negative metallic base plate 74, washer combination 76, the LEDS 5 ~~is~~ are a combination of ~~the~~ embodiments 3 and 4. The positive and negative terminal pins of the LEDS 5 enclosed in the molded structure are respectively welded to the positive and negative ~~PCB 37~~ copper foil of the PCB 37, which is coupled to ~~formed~~ an a C1 connector 152, and then the C1 connector 152 is ~~screw~~ threadedly engaged, (or may use an externally threaded

connector 121) to the upper portion of the trunk 8 (see fig. 23A). The trunk 8 which sustains the flower 23 or other equivalents, may ~~fit~~ have its root portion fit into a receptacle 72, whose inner hole is jointed to the positive terminal pins 29 of the negative copper alloy tube 73. A welding terminal plate belonging to the positive terminal pins 29 is connected to the power supply switch 11.

The trunk 8 ~~entrains~~ supports a decorative foliage 70 ~~on~~ at its top, and its root is inserted into the negative copper alloy tube 73 which is fixed with a nut and washer combination 76 to a hole formed on the negative metallic base plate ~~[[72]]~~ 74, and the root of the trunk 8 and the negative copper alloy tube 73 are firmly pressed together with a coil spring 71. With this arrangement, the trunk 8 ~~entraining~~ holding various flowers and foliage can be sustained on the pot.

Referring to Figs. 51 through 52, in order to shorten the time required for welding the colored LEDs 5 on the PCB 37 or the FPC 117 and facilitate sealing ~~then~~ them in the molded transparent resin structure, ~~the most of the confusing~~ a reduced number of terminal pins of ~~the~~ most of the LEDs 5 are ~~not used,~~ instead of them provided. Instead, a plurality of R.G.B original

color light emission dies 157 and their control IC 155 are implanted by silver ~~soldering~~ soldering directly on the PCB 37 or the FPC 117, using ~~an~~ automatic ~~implanter~~, ~~then afterwards~~ insertion. Subsequently, both the light emission dies 157 and the control IC 155 are covered with an epoxy resin cover 158 formed into a semi-spherical light focusing structure or a ~~convexed~~ rectangular light diffusing structure having a convex portions. The negative copper foil formed on the rear surface of the PCB 37 or the FPC 117 is welded to the upper terminal of an internally or externally thread tubular connector, an A type connector 31, or a B type connector. Alternately, alternatively it can be bolted to or fitted into the submain tube end. In order to adjust a light projection angle, scored lines 156 and fold lines 159 are provided on the FPC substrate 117.

(Embodiment 7)

Referring to Fig. 25 and 26, this embodiment is a combination of the former ~~the~~ embodiment 3 using the A connector 31 and the A receptacle 32, and ~~the~~ embodiment 4 using the B connector 34 and the B receptacle 35, the C1 connector 152 is ~~screw~~ threadedly engaged, (or may use an externally threaded connector 121) to the upper portion of the

trunk. A dwarf cactus 81 may be ~~disposed according to the way~~
~~described above~~ included using methods previously described.
For ~~disposing~~ a tall cactus 113 and artifact 38 (see Figs. 25,
13), an elongated strip shaped hard or soft circuit board 115 is
installed in the ~~molded~~ molded transparent resin structure. The ~~The~~ ~~;~~
~~the~~ negative copper foil of the circuit board 115 is welded to a
copper alloy clamp 112 which is clamped to a base plate 78 with
a ~~screw~~ threaded nut. For those medium sized flowers 23, leaf
blades 24 etc. a flexible irregular circuit board 117 is sealed in
the molded structure (see Figs. 43, 47) and fitted to the
receptacles 32, 35 or ~~screw~~ threadedly engaged to the submain
tube end. The LEDS 5 for illuminating the butterfly 16, the
dragonfly or the flying bird, ~~they~~ may be fixed to the base plate
78 of the medium or small sized PCB using G1, G3, G4 slim
alloy copper tubes 4 and copper alloy joints ~~their plugs~~ 132.
Besides, the root of the trunk 8 ~~entraining~~ supporting the flower
23, such as an Alice orchid 80 or a cottlea SP. 79, is inserted
into and welded to the through hole of the base plate 78. Hair-
like artificial coniferous pine leaves or spadix flowers may be
formed of ~~the~~ optical fibers 40 ~~whose~~ having one end is bound
to the molded transparent resin structure 77, as shown in Figs.

26 and 26A. The ~~, the~~ molded transparent resin structure 77 comprises a plurality of automatically color variable LEDS 5, the plant trunk of A connector 31, the A receptacle 32 and the B connector 34, the B receptacle 35. The ~~formed, the~~ colored light is directed from the molded structure 77 by the optical fiber to its exposed round head.

(Embodiment 8)

Referring to Figs. 27 and 28, the present invention comprises the metallic tubular ~~submian~~ submain 14, molded transparent resin structure 23, 24, 55, a butterfly 16, [[a]] electrically insulated ~~insulation~~ conductors 2, a bonsai pot 91, a lid 92, a fog generator 93, a water level detector 94, a microswitch 95, a ~~submergible~~ submersible pump 96, a sponge groove 111, A connector 31, A receptacle 32, B connector 34, B receptacle 35, base connectors 22, ~~the~~ and a C1 connector 152. The C1 connector is ~~screw~~ threadedly engaged, (or may use an externally threaded connector 121) to the upper portion of the trunk, the colored soft plastic bushing 33 is compressed onto the embodiment 3 structure using the A connector 31 and the A receptacle 32 and onto the embodiment 4 structure using the B connector 34 and the B receptacle 35, the trunk 8 ~~entrains~~

supports a decorative foliage 70 ~~on~~ at its top, the metallic tubular ~~submain~~ submain 14 is fixed to a negative metallic base plate 74 with a nut and washer combination 75, the negative metallic base plate 74 is fixed into ~~said~~ a bonsai pot 91 with a binder made of mixed resin and ~~ballasts~~ a ballast material. This ~~the~~ embodiment comprises a bonsai pot 91 molded ~~of~~ from a mixture of resin with stone powder and fiber glass. A ~~[[, a]]~~ water basin 99 is placed beneath the bonsai pot 91, the weight of water basin 99 is being sustained with its barrier plate 52, which is also capable of positioning the water basin so that it does not ~~to~~ move. The water basin 99 also has a lid 92. ~~the~~ The bonsai pot 91 includes a colored miniature landscape model 56, a pond 100, and an artifact 55. The pond 100 contains a fog generator 93, refined oil and water 98 therein it. The water basin 99 contains a water level detector 94, a submergible pump 96, water, a float 90, and a microswitch 95. If the water level of the pond 100 is too high, the excessive water over flows out ~~of~~ through an overflow port 131 and returns to the water basin 99. The scenic display ~~of a scenery~~ of a water ~~screen~~ scene and recycling water flow on the bonsai pot 91 is served by actuating the fog generator 93 and the pump 96 with the control of the

~~micorswitch~~ microswitch 95. When the water level of the pond 100 is too low, the microswitch 95 will trip to interrupt the power supply in accordance with the descending of the float 90 caused by the lowering of the water and refined oil 98 level.

A ~~bunch~~ plurality of slim vines are inserted on a sponge 97 of sponge groove 111 ~~so as~~ to serve as a ~~suspention~~ ~~mustache~~ hanging ornament 82. The ~~the~~ metallic tubular submain 14 are fixed ~~on~~ in the lower chamber 26 to one positive terminal of the power supply switch 11, the ~~negative~~ other terminal ~~thereof~~ switch is connected to the positive terminal of the base connector 22.

(Embodiment 9)

Referring to Fig. 38, the present invention comprises the metallic tubular ~~submain~~ submain 14, molded transparent resin structures 23, 24, and 55, a electrically insulated ~~insulation~~ conductors 2, A connector 31, A receptacle 32, B connector 34, B receptacle 35, base connectors 22, miniature landscape model 56, negative metallic base plate 74, sponge groove 111, copper alloy joints 132, and main tube connector 133. The ~~the~~ metallic tubular submain 14 ~~which being a bunch of~~ includes a plurality of flexible and various sized metallic copper conductor

tubes, copper alloy tubes, or metal plated (silver or tin) tubes welded together. ~~In~~, ~~in~~ this embodiment, the tip of the trunk 8 is ~~joined~~ joined with a main tube connector 133 by welding or ~~screw engaging~~ threaded connection 138. Several ~~screw passing~~ threaded holes 139 provided on the top of the main tube connector 133 are welded to, or ~~screw~~ threadedly engaged with ~~by~~ several copper alloy tubes 4 which ~~being~~ are covered with the molded transparent resin structure of the flower leaf, flying bird, or dragonfly (see Fig. 39). A ~~[[, a]]~~ cone shaped or a funnel shaped molded transparent resin structure 151 may be formed beneath the rear of the leaf blade so as to accommodated the LEDS 5 and a PCB. A ~~[[, a]]~~ PCB 37 using the A connector 31 and the A receptacle 32 ~~and or~~ the structure of embodiment 4 using the B connector 34 and the B receptacle 35 is provided. ~~the~~ The LEDS 5, which ~~being~~ are connected in parallel, are formed on a copper foil at the upper/lower surface of the PCB 37, and one end of the copper alloy tube 4 is welded to the center portion of the negative copper foil provided beneath the PCB (see Fig. 40G1). The artifact 55, such as an artificial molded transparent resin structure of a bear statue ~~raccoon idol~~ is inlaid in the miniature landscape model 56 (see Fig. 38), For

decoration of the miniature ~~lands-cape~~ landscape 56 and pots 13, instead of a sponge groove 111, a ~~bunch~~ plurality of slim vines are inserted on a sponge 97 so as to serve as a ~~suspension~~ mustache hanging ornament 82.

The metallic tubular submains 14 are fixed on the lower chamber 26 to one positive terminal of the power supply switch 11, the ~~negative~~ other terminal ~~thereof~~ of the switch is connected to the positive terminal of the base connector 22.

Many changes and modification in the above described embodiments of the invention can, of course, be carried out without departing from the scope thereof. Accordingly, to promote the progress in science and the useful arts, the invention is disclosed and is intended to be limited only by the scope of the appended claims.